

Cat.6 23AWG Gold Plating Patch Keystone Jack Module.



ITEM	SPECIFICATION
Plating Material	: Gold plating option (3U",6U",15U",30U",50U") over Nickel
PCB material	: FR-4 T=1.6mm
Housing Color	: White
Housing Material	: ABS or PC
Housing Flammability Rating	: UL 94V-0
Workable wire gauge	: 23AWG
Industry Standards	: RoHS compliant, TIA/CAT5E, 568A/568B
Angle	: 90 Degree
Termination	: Krone Type

Electrical		
■ Voltage Rating :		125 VAC RMS
■ Current Rating :		1.5AMP
■ Contact Resistance:		110 Milliohs MAX.
■ Insulation Resistance:		1000 megohms MIN 500 VDC
■ Dielectric Strength :		750 VAC RMS 60Hz ,1 MIN

Environment		
■ Storage:		- 40~ 85°c
■ Operation:		0~70°c
■ Housing Material:		PBT-UL90V-0
■ Panel Frame:		Carbon Steel, Powder Coating
■ Contact Material:		PC-UL90V-0
■ Contact:		Gold plating

Mechanical		
■ RJ45 Jack:		IFE: 750 times MIN.
■ IDC Life:		200 times MIN.
■ Wire:		AWG 23
■ Tia Cat.5e Perm Link Test:		Worst Pair NEXT Margin ≥3dB
■ Retentiveness of insertion structure:		50N 60±5s

