

Cat.6A 23AWG Gold Plating Patch Keystone Jack Module.



ITEM

SPECIFICATION

Plating Material	: Gold plating option (3U",6U",15U",30U",50U") over Nickel	
PCB material	: FR-4 T=1.6mm	
Housing Color	: White	
Housing Material	: ABS or PC	
Housing Flammability Rating	: UL 94V-0	
Workable wire gauge	: 23AWG	
Industry Standards	: RoHS compliant, TIA/CAT5E, 568A/568B	
Angle	: 90 Degree	
Termination	: Krone Type	
Electrical	<ul style="list-style-type: none"> ANSI/TIA Category Contact Resistance Variation, maximum Contact Resistance, maximum Current Rating Dielectric Withstand Voltage, RMS, conductive surface Dielectric Withstand Voltage, RMS, contact-to-contact Insulation Resistance, minimum 	6A 20 mOhm 100 mOhm 1.5 A @ 20 °C 1.5 A @ 68 °F 1500 Vac @ 60 Hz 1000 Vac @ 60 Hz 500 MOhm
Environment	<ul style="list-style-type: none"> Flammability Rating Operating Temperature Relative Humidity Safety Standard Storage Temperature 	UL 94 V0 10°C to +60 °C (+14 °F to +140 °F) Up to 95%, noncondensing cUL UL 40°C to +70 °C (40°F to +158 °F)
Mechanical	<ul style="list-style-type: none"> Conductor Gauge, solid Conductor Gauge, stranded Conductor Type Material Type Outlet/Module Contact Plating Plug Insertion Life, minimum Plug Insertion Life, test plug Plug Retention Force, minimum Rear Termination Contact Plating Rear Termination Type Wiring 	22 AWG 24 AWG 22 AWG 24 AWG Solid Stranded (7 strands) Copper alloy Highimpact, flame retardant, thermoplastic Precious metals 750 times IEC 606037compliant plug 30 lbf 133 N Nickel IDC T568A T568B

